Tender Specification STRAUB-PLAST-PRO



Water and waste water, industrial plants and maintenance

STRAUB-PLAST-PRO® - Axially restrained full set allowing a quick and simple installation of pressure pipes made of Polyethylene (PE). The full sets are available for pipes in dimension SDR 11 (63.0 mm- 110.0 mm) and SDR 17(>110.0 mm - 355.0 mm). The pipes made of PE 80 or PE 100 are being connected by using a liner (e.g. coupler, reducer, elbow 45°, elbow 90°, Equal Tees, Flanged Branch Tees) and two connectors.

Connectors up to OD 160.0 mm - stainless steel DIN 1.4404 Connectors from OD180.0 mm - stainless steel DIN 1.4462 Duplex Liner - steel ST 52 with Rilsan coated

Product	STRAUB-PL	.AST-PRO

Pipe OD (max. 355 mm):mm

Tube serial no: SDR11 □ / SDR17 □

Liner:



Manufacturer STRAUB WERKE AG

7323 Wangs / Switzerland Tel. +41 81 725 41 00 Fax. +41 81 725 41 01

www.straub.ch

Supplier

(Address of STRAUB Distributor)

Remarks

- Working pressure at 20°C for pipes SDR 11 = 16 bar, for pipes SDR 17 = 10 bar. If the temperature will constantly exceed 20°C, the working pressures according to DIN 8074 have to be
- Installation temperature -5°C up to 40°C. 2.
- Usually no pipe end treatment necessary. 3.
- At the risk of corrosion, the use of bandages or shrink sleeves approved on the market is recommended.
- Stiffening ring integrated in the full set 5.
- Suitable for the connection of multi-layer pipes.

Important

Only for PE pipes according to EN12201-2 / DIN8074. Installation on all other plastic pipes tubes, after consultation with Straub Werke AG only. Connection of plastic pipes with diameter differences (pipe tolerances) according to EN12201-2 / DIN8074.