


STRAUB-CLAMP®

One-piece and two-piece stainless steel repair clamp
Its unique design principle enables rapid and safe
installation. The special lip profile design enables a
secure seal, even on corroded pipe surfaces.



Range of dimensions : DN 40 – DN 400

Tender Specifications

STRAUB-CLAMP®

For easy repair of pipelines, made of: Steel, cast iron, ductile cast iron, fibrous cement and PVC.

Working pressures: Gas: PN 5 (max. DN 300)
 Water: independent of dimensions (see applicable price list)
 max. PN 16

Seal: NBR

Applications: Gas and drinking water supply lines
 Pressurized sewers
 Industrial piping

Item	No.	Text	Price per Unit	Total Price
1.1		<p>STRAUB-CLAMP® SCE Stainless Steel One-Piece Repair Clamp</p> <p>To seal damaged gas and water lines that are made of steel, cast iron, ductile cast iron, fibrous cement, PVC Manufactured without any thermal treatment or welded parts. Locking bolts consist of individual bolts threaded into nuts.</p> <p>Working pressures: Gas PN 5 (max. DN 300) Water, depends on dimensions (see applicable price list) max. PN 16</p> <ul style="list-style-type: none"> - Housing and locking mechanism of V2A stainless steel - Bolts and nuts made of coated stainless steel - Sealing material NBR for gas, water and wastewater - Diameter range: max. / ca.10mm - The components must be used according to STRAUB-CLAMP® installation instructions - Removal and reinstallation possible 		

Item	No.	Text	Price per Unit	Total Price
		STRAUB-CLAMP® SCE Stainless Steel One-Piece Repair Clamp		
		DN	Diameter Range in mm	Installed Length in mm
		40	44-48	200
		40	44-48	300
		40	48-52	200
		40	48-52	300
		50	54-58	200
		50	54-58	300
		50	60-67	200
		50	60-67	300
		65	70-77	200
		65	70-77	300
		65	75-83	200
		65	75-83	300
		80	82-89	200
		80	82-89	300
		80	82-89	400
		80	87-95	200
		80	87-95	300
		80	87-95	400
		80	88-98	200
		80	88-98	300
		100	95-104	200
		100	95-104	300
		100	95-104	400
		100	108-118	200
		100	108-118	300
		100	108-118	400
		100	113-123	200
		100	113-123	300
		100	113-123	400
		100	118-128	200
		100	118-128	300
		100	118-128	400
		100	120-131	200
		100	120-131	300
		125	132-142	200
		125	132-142	300
		125	132-142	400
		125	135-145	200
		125	135-145	300
		125	139-149	200
		125	139-149	300
		125	145-155	200
		125	145-155	300

Item	No.	Text			Price per Unit	Total Price
		STRAUB-CLAMP® SCE Stainless Steel One-Piece Repair Clamp				
		DN	Diameter Range in mm	Installed Length in mm		
		150	159-170	200		
		150	159-170	300		
		150	159-170	400		
		150	167-178	200		
		150	167-178	300		
		150	167-178	400		
		150	176-187	200		
		150	176-187	300		
		150	176-187	400		
		175	193-203	200		
		175	193-203	300		
		200	215-225	200		
		200	215-225	300		
		200	215-225	400		
		200	228-239	300		
		225	240-250	300		
		250	250-260	300		
		250	261-271	300		
		250	269-280	300		
		250	280-291	300		
		300	315-325	300		
		300	320-330	300		

Item	No.	Text	Price per Unit	Total Price																																																																																													
1.2		<p>STRAUB-CLAMP® SCZ Stainless Steel Two-Piece Repair Clamp</p> <p>To seal damaged gas and water lines that are made of steel, cast iron, ductile cast iron, fibrous cement, PVC Manufactured without any thermal treatment or welded parts. Locking bolts consist of individual bolts threaded into nuts. Working pressures: Gas PN 5 (max. DN 300) Water, depends on dimensions (see applicable price list) max. PN 16</p> <ul style="list-style-type: none"> - Housing and locking mechanism of V2A stainless steel - Bolts and nuts made of coated stainless steel - Sealing material NBR for gas, water and wastewater - Diameter range: max. / ca.20mm - The components must be used according to STRAUB-CLAMP® installation instructions - Removal and reinstallation possible 																																																																																															
		<table border="1"> <thead> <tr> <th>DN</th> <th>Diameter Range in mm</th> <th>Installed Length in mm</th> </tr> </thead> <tbody> <tr><td>80</td><td>88-110</td><td>200</td></tr> <tr><td>80</td><td>88-110</td><td>300</td></tr> <tr><td>80</td><td>88-110</td><td>400</td></tr> <tr><td>100</td><td>100-120</td><td>200</td></tr> <tr><td>100</td><td>100-120</td><td>300</td></tr> <tr><td>100</td><td>100-120</td><td>400</td></tr> <tr><td>100</td><td>108-128</td><td>200</td></tr> <tr><td>100</td><td>108-128</td><td>300</td></tr> <tr><td>100</td><td>108-128</td><td>400</td></tr> <tr><td>100</td><td>114-134</td><td>200</td></tr> <tr><td>100</td><td>114-134</td><td>300</td></tr> <tr><td>100</td><td>114-134</td><td>400</td></tr> <tr><td>125</td><td>120-140</td><td>200</td></tr> <tr><td>125</td><td>120-140</td><td>300</td></tr> <tr><td>125</td><td>120-140</td><td>400</td></tr> <tr><td>125</td><td>130-150</td><td>200</td></tr> <tr><td>125</td><td>130-150</td><td>300</td></tr> <tr><td>125</td><td>130-150</td><td>400</td></tr> <tr><td>150</td><td>140-160</td><td>200</td></tr> <tr><td>150</td><td>140-160</td><td>300</td></tr> <tr><td>150</td><td>140-160</td><td>400</td></tr> <tr><td>150</td><td>159-180</td><td>200</td></tr> <tr><td>150</td><td>159-180</td><td>300</td></tr> <tr><td>150</td><td>159-180</td><td>400</td></tr> <tr><td>150</td><td>168-189</td><td>200</td></tr> <tr><td>150</td><td>168-189</td><td>300</td></tr> <tr><td>150</td><td>168-189</td><td>400</td></tr> <tr><td>175</td><td>190-210</td><td>200</td></tr> <tr><td>175</td><td>190-210</td><td>300</td></tr> <tr><td>175</td><td>190-210</td><td>400</td></tr> </tbody> </table>	DN	Diameter Range in mm	Installed Length in mm	80	88-110	200	80	88-110	300	80	88-110	400	100	100-120	200	100	100-120	300	100	100-120	400	100	108-128	200	100	108-128	300	100	108-128	400	100	114-134	200	100	114-134	300	100	114-134	400	125	120-140	200	125	120-140	300	125	120-140	400	125	130-150	200	125	130-150	300	125	130-150	400	150	140-160	200	150	140-160	300	150	140-160	400	150	159-180	200	150	159-180	300	150	159-180	400	150	168-189	200	150	168-189	300	150	168-189	400	175	190-210	200	175	190-210	300	175	190-210	400		
DN	Diameter Range in mm	Installed Length in mm																																																																																															
80	88-110	200																																																																																															
80	88-110	300																																																																																															
80	88-110	400																																																																																															
100	100-120	200																																																																																															
100	100-120	300																																																																																															
100	100-120	400																																																																																															
100	108-128	200																																																																																															
100	108-128	300																																																																																															
100	108-128	400																																																																																															
100	114-134	200																																																																																															
100	114-134	300																																																																																															
100	114-134	400																																																																																															
125	120-140	200																																																																																															
125	120-140	300																																																																																															
125	120-140	400																																																																																															
125	130-150	200																																																																																															
125	130-150	300																																																																																															
125	130-150	400																																																																																															
150	140-160	200																																																																																															
150	140-160	300																																																																																															
150	140-160	400																																																																																															
150	159-180	200																																																																																															
150	159-180	300																																																																																															
150	159-180	400																																																																																															
150	168-189	200																																																																																															
150	168-189	300																																																																																															
150	168-189	400																																																																																															
175	190-210	200																																																																																															
175	190-210	300																																																																																															
175	190-210	400																																																																																															

Item	No.	Text			Price per Unit	Total Price
		STRAUB-CLAMP® SCZ Stainless Steel Two-Piece Repair Clamp				
		DN	Diameter Range in mm	Installed Length in mm		
		200	210-230	200		
		200	210-230	300		
		200	210-230	400		
		200	218-238	200		
		200	218-238	300		
		200	218-238	400		
		225	240-260	200		
		225	240-260	300		
		225	240-260	400		
		250	269-289	200		
		250	269-289	300		
		250	269-289	400		
		275	282-302	200		
		275	282-302	300		
		275	282-302	400		
		300	315-335	200		
		300	315-335	300		
		300	315-335	400		
		300	322-344	200		
		300	322-344	300		
		300	322-344	400		
		350	337-358	300		
		350	337-358	400		
		350	347-367	300		
		350	347-367	400		
		350	365-385	400		
		400	410-430	400		
		400	420-440	400		

All information represents the current design as of the date of this printing. We reserve the right to make changes for purposes of technical improvements. We are not responsible for print errors.

Date: 12.2006